



(949) 225-0000

Downlight JB Series

Description:

Luna Sciences new LED commercial downlight series have been optimized to the third generation. The innovative combined design of junction box and housing makes it more flexible as it is designed and engineered for recessed application in variety of applications.

It provides a 70 degree beam angle to fulfill a wide range of lighting needs such as offices, shopping malls, hospitals, airport, hotel lobbies and more. Easy fit installation comes from adjustable spring action housing clips. Optional Square Trim as well as optional T-bar support plate is available to meet your indoor application needs



Model	DLJB-4W20K00	DLJB-6W30K00
Efficacy	1,600lm	2,650lm
Rated Power	20W	30W

4" & 6"

Technical data:

Input Voltage	120-277VAC
CCT Options	3000K, 3500K, 4000K, 5000K
CRI	80
THD	<20%
PF	>.90
Standard Warranty	5 years
Lifetime Warranty	Designed for min. 50,000 hours
Mounting	Recessed
Temperature Rating	45 degree C & below room side and plenum side
Dimming Type	0-10V Dimming
Recommended Dimmers	DVTV [Lutron], IP710[Levitron]
Damp Rated	Yes
UL Listed	Yes

Direct connect to AC inline. Suitable for drywall ceiling without the use of brackets. Suitable for T-bar installation using a flat bracket for the 4" an 6" with seismic connection tabs and or cable assembly

